

90° HYBRID


SURFACE MOUNT MODEL: SLQ-301

3:1 BANDWIDTH

5.5 - 16.5 MHz

FEATURES:

- ▶ Excellent Performance
- ▶ Small Size, Surface Mount
- ▶ Building Block For:
 - Power Amplifiers
 - Image Rejection Mixers
 - I & Q / SSB Modulators
 - Phase Shifters & More...



SPECIFICATIONS

Frequency	5.5 - 16.5 MHz	
Insertion Loss (dB) *	Typ.	Max.
	0.3	0.5
Amplitude Unbalance	Typ.	Max.
	0.9	1.2
Phase Unbalance	Typ.	Max.
	1°	3°
Isolation (dB)	Typ.	Min.
	23	20
Input Power	1 Watt (Max.)	
Impedance	50 Ohms (Nom.)	
VSWR	1.10:1 (Typ.)	
Operating Temperature Range	-40 to +85 °C	
Storage Temperature Range	-55 to +100 °C	

* Insertion loss is the average loss of the 2 coupling values in excess of the theoretical 3 dB coupling.

Package #	159LF
-----------	-------

TOLERANCES ON THREE DECIMAL PLACES= ± 0.015
PACKAGE MOUNTING: SEE APPLICATION NOTES AN7200 & AN7301

Port Configuration				
Input	Isolated*	+90° Output	0° Output	GND.**
6	5	1	2	3,4

* Terminate ISOLATED port in 50 Ohms EXTERNALLY.
** Ground Externally



90° HYBRID

SURFACE MOUNT MODEL: SLQ-301

3:1 BANDWIDTH

5.5 - 16.5 MHz

Data @ 25°C



PERFORMANCE PLOTS





90° HYBRID

SURFACE MOUNT MODEL: SLQ-301

3:1 BANDWIDTH

5.5 - 16.5 MHz

Data @ 25°C



PERFORMANCE PLOTS




90° HYBRID

SURFACE MOUNT MODEL: SLQ-301

3:1 BANDWIDTH

5.5 - 16.5 MHz

Data @ 25°C



PERFORMANCE PLOTS

