

# 90° HYBRID


## SURFACE MOUNT MODEL: SMQ-C04

**OCTAVE BANDWIDTH**

**100 - 200 MHz**

**FEATURES:**


- ▶ Excellent Performance
- ▶ Small Size, Surface Mount
- ▶ Building Block For:
  - Power Amplifiers
  - Image Rejection Mixers
  - I & Q / SSB Modulators
  - Phase Shifters & More...



**SPECIFICATIONS (Rev. C 06/20/22)**

Frequency	100 - 200 MHz	
Insertion Loss (dB) *	Typ.	Max.
	0.6	0.9
Amplitude Unbalance	Typ.	Max.
	0.5	1.0
Phase Unbalance	Typ.	Max.
	1°	4°
Isolation (dB)	Typ.	Min.
	28	18
Power Rating	1 Watt (Max.)	
Impedance	50 Ohms (Nom.)	
VSWR	1.1:1 (Typ.)	
Operating Temperature Range	-40 to +85 °C	
Storage Temperature Range	-55 to +100 °C	

\* Insertion loss in excess of the theoretical 3 dB coupling.



Port Configuration					
Input	Isolated*	+90° Output	0° Output	GND.**	No Conn.
5	6	1	2	7,8,9,10	3,4

\* Terminate ISOLATED port in 50 Ohms EXTERNALLY.  
 \*\* Ground Externally



# 90° HYBRID

## SURFACE MOUNT MODEL: SMQ-C04

OCTAVE BANDWIDTH

100 - 200 MHz

Data @ 25°C



PERFORMANCE PLOTS



# 90° HYBRID

## SURFACE MOUNT MODEL: SMQ-C04

OCTAVE BANDWIDTH

100 - 200 MHz

Data @ 25°C



PERFORMANCE PLOTS


# 90° HYBRID

## SURFACE MOUNT MODEL: SMQ-C04

OCTAVE BANDWIDTH

100 - 200 MHz

Data @ 25°C



PERFORMANCE PLOTS