

TRIPLE-BALANCED MIXER

SURFACE MOUNT MODEL: STM-6000

WIDE BANDWIDTH


1-6000 MHz

FEATURES:

- ▶ High Performance
- ▶ High Interport Isolation
- ▶ Broad Bandwidth IF

APPLICATIONS:

- ▶ Narrow Band & Broadband Up/Down Conversion.



SPECIFICATIONS

Frequency (MHz)	LO/RF 1 - 6000	IF 1 - 4000	
Conversion Loss (dB)	Freq (MHz)	Typ.	Max.
	1 - 200	8.3	9.0
	200 - 3000	8.5	10.0
	3000 - 6000	10.5	11.8
Isolation (dB)	LO/RF		
	Typ.	Min.	
	34	23	
	LO/IF		
	Typ.	Min.	
	30	23	
RF/IF			
Typ.	Min.		
24	17		
LO Power¹	+15 to +23 dBm (Nom.)		
1 dB Compression Point	+11 dBm (Typ.)		
Input IP³	+21 dBm (Typ.) ¹		
Impedance	50 Ohms (Nom.)		
Operating Temperature Range	-40 to +85 °C		

¹ Typical measurements made with LO at +15 dBm. Improves with higher LO drive.

Package # 357

RECOMMENDED PCB LAYOUT

TOLERANCES ON THREE DECIMAL PLACES = ± 0.015

PACKAGE MOUNTING: SEE APPLICATION NOTE AN7301

PORT CONFIGURATION			
RF	LO	IF	GND
8	4	6	All Other



TRIPLE-BALANCED MIXER

SURFACE MOUNT MODEL: STM-6000

WIDE BANDWIDTH

1-6000 MHz

PERFORMANCE PLOTS





TRIPLE-BALANCED MIXER

SURFACE MOUNT MODEL: STM-6000

WIDE BANDWIDTH

1-6000 MHz

PERFORMANCE PLOTS





TRIPLE-BALANCED MIXER

SURFACE MOUNT MODEL: STM-6000

WIDE BANDWIDTH

1-6000 MHz

PERFORMANCE PLOTS




TRIPLE-BALANCED MIXER

SURFACE MOUNT MODEL: STM-6000

WIDE BANDWIDTH

1-6000 MHz



PERFORMANCE PLOTS