VOLTAGE CONTROLLED OSCILLATOR
SURFACE MOUNT MODEL: DCMO100230-5

WIDE BANDWIDTH — 1000 - 2300 MHz

FEATURES:

- Exceptional Phase Noise Performance
- Small Size, Surface Mount
- Lead Free Patented REL-PRO® Technology

Phase Noise



SPECIFICATIONS (Rev. E 04/23/09)

Frequency	1000 - 2300 MHz
Tuning Voltage	See table below.
Bias Voltage	+5 VDC @ 35 mA (Nom.)
Output Power	+3 dBm (Min.)
Tuning Sensitivity	70 MHz/V (Typ.)
Output Impedance	50 Ohms (Nom.)
Harmonic Suppression	10 dB (Typ.)
Frequency Pulling	3 MHz (Max. @ 1.75:1 VSWR)
Frequency Pushing	2 MHz/V (Max.)
Tuning Port Capacitance	115 pF (Typ.)
Phase Noise @ 10 kHz	-98 dBc/Hz (Typ.)
Operating Temperature Range	-40 to +85 °C
** Internally regulated*	

Guaranteed Tuning Specifications

Tuning Voltage (V)	Frequency (MHz)
0.5	1000 (Max)
5	1250 (Min)
8	1450 (Min)
12	1650 (Min)
15	1800 (Min)
18	2000 (Min)
24	2300 (Min)

Absolute Maximum Ratings

Storage Temp. Range	-55 to +125 ºC
Bias Voltage	+5.5 V
Tuning Voltage	+26 V
DC Voltage Applied to RF Out	± 25 V

Package #	278LF



This product is manufactured under one or more of the following patents. Approved: 5,160,810; 5,122,621; 5,390,349; 5,416,449; 5,650,754; 5,805,431; 6,525,623; 6,850,575; 7,088,189; 7,180,381; 7,196,591; 7,262,670; 7,265,642; 7,292,113; 7,365,612; 7,495,525; 2,548,311; 2,548,317; 7,545,229; 7,580,693; 7,586,381; 7,605,670; 7,636,021; 2,533,623 | Pending: 60/493075; 60/501371 & 60/501790; 60/527957 & 60/528670; 60/563481; 60/564173; 60/589090; 60/601823; 60/605791; EV31369834; 11/259766; 60/622485 & 60/710310; 10/937525/60/736901; 60/732787; 7,495,525; 2,548,311; 2,548,317; 7,545,229; 2,563,174; 7,580,693; 7,612,296; 2,524,751

Copyright © Synergy Microwave Corporation

201 McLean Boulevard • Paterson, New Jersey 07504 USA • Tel: (973) 881-8800 • Fax: (973) 881-8361
E-Mail: sales@synergymwave.com • World Wide Web: http://www.synergymwave.com

SYNERGY® MICROWAVE CORPORATION

VOLTAGE CONTROLLED OSCILLATOR
SURFACE MOUNT MODEL: DCMO100230-5

WIDE BANDWIDTH **1000 - 2300 MHz**

PERFORMANCE PLOTS





This product is manufactured under one or more of the following patents. Approved: 5,160,810; 5,122,621; 5,390,349; 5,416,449; 5,650,754; 5,805,431; 6,525,623; 6,850,575; 7,088,189; 7,180,381; 7,196,591; 7,262,670; 7,265,642; 7,292,113; 7,365,612; 7,495,525; 2,548,311; 2,548,317; 7,545,229; 7,580,693; 7,586,381; 7,605,670; 7,636,021; 2,533,623 | Pending: 60/493075; 60/501371 & 60/501790; 60/527957 & 60/528670; 60/563481; 60/564173; 60/589090; 60/601823; 60/605791; EV31369834; 11/259766; 60/622485 & 60/710310; 10/937525/60/736901; 60/732787; 7,495,525; 2,548,311; 2,548,317; 7,545,229; 2,563,174; 7,580,693; 7,612,296; 2,524,751

Copyright © Synergy Microwave Corporation

201 McLean Boulevard • Paterson, New Jersey 07504 USA • Tel: (973) 881-8800 • Fax: (973) 881-8361
E-Mail: sales@synergymwave.com • World Wide Web: http://www.synergymwave.com

SYNERGY® MICROWAVE CORPORATION

VOLTAGE CONTROLLED OSCILLATOR
SURFACE MOUNT MODEL: DCMO100230-5

WIDE BANDWIDTH **1000 - 2300 MHz**

PERFORMANCE PLOTS





This product is manufactured under one or more of the following patents. Approved: 5,160,810; 5,122,621; 5,390,349; 5,416,449; 5,650,754; 5,805,431; 6,525,623; 6,850,575; 7,088,189; 7,180,381; 7,196,591; 7,262,670; 7,265,642; 7,292,113; 7,365,612; 7,495,525; 2,548,311; 2,548,317; 7,545,229; 7,580,693; 7,586,381; 7,605,670; 7,636,021; 2,533,623 | Pending: 60/493075; 60/501371 & 60/501790; 60/527957 & 60/528670; 60/563481; 60/564173; 60/589090; 60/601823; 60/605791; EV31369834; 11/259766; 60/622485 & 60/710310; 10/937525/60/736901; 60/732787; 7,495,525; 2,548,311; 2,548,317; 7,545,229; 2,563,174; 7,580,693; 7,612,296; 2,524,751

Copyright © Synergy Microwave Corporation

201 McLean Boulevard • Paterson, New Jersey 07504 USA • Tel: (973) 881-8800 • Fax: (973) 881-8361
E-Mail: sales@synergymwave.com • World Wide Web: http://www.synergymwave.com

SYNERGY® MICROWAVE CORPORATION