

BI-DIRECTIONAL COUPLER


SYNSTRIP® MODEL: SCS-2125D

WIDE BANDWIDTH

2100 - 2500 MHz


FEATURES:

- ▶ SYNSTRIP® Technology
- ▶ Small Size, Surface Mount
- ▶ Optimum Performance



SPECIFICATIONS (Rev. B 08/21/07)

Frequency	2100 - 2500 MHz	
Coupling	20 dB ±1 dB (Nom.)	
Mainline Loss	0.25 dB (Max.) *	
Directivity	dB (Typ.)	dB (Min.)
	22	20
Frequency Sensitivity	±0.30 dB (Max.)	
Power Rating	100 Avg. Watts (CW Max.)	
Output Impedance	50 Ohms (Nom.)	
VSWR	dB (Typ.)	dB (Max.)
	1.18:1	1.20:1
Operating Temperature Range	-55 to +85 °C	
* Excluding coupling loss		





BI-DIRECTIONAL COUPLER

SYNSTRIP[®] MODEL: SCS-2125D

WIDE BANDWIDTH

2100 - 2500 MHz

PERFORMANCE PLOTS



BI-DIRECTIONAL COUPLER

SYNSTRIP[®] MODEL: SCS-2125D

WIDE BANDWIDTH

2100 - 2500 MHz

PERFORMANCE PLOTS

