

DIELECTRIC RESONATOR OSCILLATOR


SURFACE MOUNT MODEL: SDRO1000-8

FREQUENCY


10 GHz

FEATURES:

- ▶ Exceptional Phase Noise Performance
- ▶ Small Size Surface Mount
- ▶ Lead Free RoHS Compliant




Phase Noise



SPECIFICATIONS (Rev. C 04/16/18)

Frequency	10 GHz	
Tuning Voltage	1 - 15 VDC	
Bias Voltage	+8 VDC @ 25 mA (Max.)	
Output Power	-2 dBm (Min.)	
Tuning Sensitivity	0.4 MHz/V (Typ.)	
Thermal Drift	2 ppm / °C (Typ.)	
Output Impedance	50 Ohms (Nom.)	
Harmonic Suppression	40 dBc (Typ.)	
Frequency Pulling	500 kHz (Typ. @ 1.75:1 VSWR)	
Frequency Pushing	500 kHz/V (Typ.)	
Tuning Port Capacitance	35 pF (Typ.)	
Modulation Bandwidth	> 20 MHz	
Phase Noise	Offset	dBc/Hz (Typ.)
	10 kHz	-107
	100 kHz	-127
	1 MHz	-147
10 MHz	-165	
Jitter	90 fs (@ 1 kHz to 30 MHz) (Typ.)	
Operating Temperature Range	-15 to +75 °C	

Package # 396




Absolute Maximum Ratings

Storage Temp. Range	-30 to +85 °C
Bias Voltage	+8.5 V
Tuning Voltage	+16 V
DC Voltage Applied to RF Out	±25 V

Notes:

1. Tuning screws are factory locked for optimum performance at the center frequency. Tuning of the mechanical screw can cause significant shifts in frequency and adversely affect overall performance. Warranty is void if seal over tuning screw is damaged.
2. Test data measured with bias voltage at +8V.
3. Specifications guaranteed at 10 GHz.

Copyright © Synergy Microwave Corporation
 201 McLean Boulevard • Paterson, New Jersey 07504 USA
 Tel: (973) 881-8800 • Fax: (973) 881-8361
 E-Mail: sales@synergymwave.com • Website: http://www.synergymwave.com
 Patents : http://www.synergymwave.com/patents





DIELECTRIC RESONATOR OSCILLATOR SURFACE MOUNT MODEL: SDRO1000-8

FREQUENCY

10 GHz

PERFORMANCE PLOTS





DIELECTRIC RESONATOR OSCILLATOR SURFACE MOUNT MODEL: SDRO1000-8

FREQUENCY

10 GHz


PERFORMANCE PLOTS



DIELECTRIC RESONATOR OSCILLATOR SURFACE MOUNT MODEL: SDRO1000-8

FREQUENCY

10 GHz



PERFORMANCE PLOTS