

INTELLIGENT INTERACTIVE SYNTHESIZER



SURFACE MOUNT MODEL: LSLO220275-625

FREQUENCY

2200 - 2750 MHz

FEATURES:

- ▶ Ultra-Low Phase Noise
- ▶ Small Size, Surface Mount
- ▶ Fast Settling Time
- ▶ Patented REL-PRO® Technology



SPECIFICATIONS (Rev. A 08/11/16)

Frequency	2200 - 2750 MHz	
Step Size	6.25 MHz	
Reference Input Frequency	100 MHz	
Reference Input Level	+5.0 dBm $\pm$ 5 dB	
Bias Voltage	Vcc 1 (Digital)	+3.3 VDC @ 550 mA (Max.)
	Vcc 2 (Vtune)	+12 VDC @ 60 mA (Max.)
	Vcc 3 (VCO)	+5 VDC @ 100 mA (Max.)
Output Power	+8 dBm (Min.)	
Spurious & Reference Sideband Suppression	Adjacent integer boundary spur ¹	65 dBc (Typ.)
	All others	> 65 dBc (Min.)
Harmonic Suppression	23 dBc (Typ.)	
Output VSWR	2.0:1 (Max.)	
Typical Phase Noise	Offset	Phase Noise
	@ 1 kHz	-118 dBc/Hz
	@ 10 kHz	-123 dBc/Hz
	@ 100 kHz	-118 dBc/Hz
	@ 1 MHz	-135 dBc/Hz
	@ 10 MHz	-155 dBc/Hz

Settling Time	<100 uSec. (With SPI Fast Lock Mode) ²
Lock Detect	Complementary CMOS (Low indicator lock)
Programming	SPI
Operating Temperature Range	-30 to +70 °C (Baseplate)

Absolute Maximum Ratings

Storage Temp. Range	-55 to + 125 °C
Bias Voltage (Digital)	+3.50 V
Bias Voltage (Vtune)	+12.5 V
Bias Voltage (VCO)	+5.5V
DC Voltage Applied to RF Out	$\pm$ 25 V

¹ Adjacent integer boundary occurs when the output frequency $F_{out} = [N \cdot F_{ref}]$. The fractional spurs decay at higher step offsets.

² From rising edge of LE to within 1/2 channel spacing.

2200 - 2750 MHz

INTELLIGENT INTERACTIVE SYNTHESIZER

SURFACE MOUNT MODEL: LSLO220275-625


FREQUENCY

2200 - 2750 MHz


Low Band Integer Operating Condition

@ 25 °C


HARMONIC SUPPRESSION



REFERENCE SIDEBAND SUPPRESSION



REFERENCE SIDEBAND SUPPRESSION



PERFORMANCE PLOTS

INTELLIGENT INTERACTIVE SYNTHESIZER

SURFACE MOUNT MODEL: LSLO220275-625


FREQUENCY

2200 - 2750 MHz


Mid Band Integer Operating Condition

@ 25 °C


HARMONIC SUPPRESSION



REFERENCE SIDEBAND SUPPRESSION



REFERENCE SIDEBAND SUPPRESSION



PERFORMANCE PLOTS

INTELLIGENT INTERACTIVE SYNTHESIZER

SURFACE MOUNT MODEL: LSLO220275-625


FREQUENCY

2200 - 2750 MHz


High Band Integer Operating Condition

@ 25 °C


HARMONIC SUPPRESSION



REFERENCE SIDEBAND SUPPRESSION



REFERENCE SIDEBAND SUPPRESSION



PERFORMANCE PLOTS

INTELLIGENT INTERACTIVE SYNTHESIZER

SURFACE MOUNT MODEL: LSLO220275-625

FREQUENCY


2200 - 2750 MHz

Low Band Fractional Boundary Operating Condition


@ 25 °C

PERFORMANCE PLOTS


HARMONIC SUPPRESSION



REFERENCE SIDEBAND SUPPRESSION



REFERENCE SIDEBAND SUPPRESSION



INTELLIGENT INTERACTIVE SYNTHESIZER

SURFACE MOUNT MODEL: LSLO220275-625


FREQUENCY

2200 - 2750 MHz


Mid Band Fractional Boundary Operating Condition

@ 25 °C


HARMONIC SUPPRESSION



REFERENCE SIDEBAND SUPPRESSION



REFERENCE SIDEBAND SUPPRESSION



PERFORMANCE PLOTS

INTELLIGENT INTERACTIVE SYNTHESIZER

SURFACE MOUNT MODEL: LSLO220275-625

FREQUENCY


2200 - 2750 MHz

High Band Fractional Boundary Operating Condition


@ 25 °C

PERFORMANCE PLOTS


HARMONIC SUPPRESSION



REFERENCE SIDEBAND SUPPRESSION



REFERENCE SIDEBAND SUPPRESSION



Copyright © Synergy Microwave Corporation
 201 McLean Boulevard • Paterson, New Jersey 07504 USA
 Tel: (973) 881-8800 • Fax: (973) 881-8361

E-Mail: sales@synergymwave.com • Website: <http://www.synergymwave.com>

Patents : <http://www.synergymwave.com/patents>

