

PHASE DETECTORS



SURFACE-MOUNT

FREQUENCY RANGE (MHz)		IMPEDANCE (Ohm)		POWER LEVEL (dBm)	ISOLATION (dB) LO/RF		DC OUTPUT (mV)		DC OFFSET (mV)	PACKAGE	PIN-OUT (See Below)	MODEL
LO/RF	OUTPUT	LO/RF	OUTPUT		MIN	TYP/MIN	TYP/MAX					
1-100	DC-50	50	500	+7	40	1000/750	0.2/1.0	134J	1	PDZ-K1		
10-200	DC-50	50	500	+7	40	1000/750	0.3/1.0	134J	1	PDZ-K2		

THROUGH HOLE MOUNT

MINI 8 PIN - RELAY CAN



FREQUENCY RANGE (MHz)		IMPEDANCE (Ohm)		POWER LEVEL (dBm)	ISOLATION (dB) LO/RF		DC OUTPUT (mV)		DC OFFSET (mV)	PACKAGE	PIN-OUT (See Below)	MODEL
LO/RF	OUTPUT	LO/RF	OUTPUT		MIN	TYP/MIN	TYP/MAX					
1-100	DC-50	50	500	+7	40	1000/750	0.2/1.0	108	2	PDP-403		
10-200	DC-50	50	500	+7	40	1000/750	0.3/1.0	108	2	PDP-402		
50-400	DC-50	50	500	+7	35	600/500	0.5/1.0	108	2	PDP-413		

8 PIN - RELAY CAN



FREQUENCY RANGE (MHz)		IMPEDANCE (Ohm)		POWER LEVEL (dBm)	ISOLATION (dB) LO/RF		DC OUTPUT (mV)		DC OFFSET (mV)	PACKAGE	PIN-OUT (See Below)	MODEL
LO/RF	OUTPUT	LO/RF	OUTPUT		MIN	TYP/MIN	TYP/MAX					
1-100	DC-50	50	500	+7	40	1000/750	0.2/1.0	102	2	PDP-201		
5-150	DC-50	50	500	+7	40	1000/750	0.3/1.0	102	2	PDP-202		

NOTE:

1. Output polarity is negative on all models.
2. Maximum RF input power, 100 mW. Peak IF current, 40mA.

PIN-OUT TABLE

	LO	RF	DC OUTPUT	GROUND	CASE GND
# 1	1	4	5	2,3,6	---
# 2	8	1	*3,4	2,5,6,7	2

*Pins must be connected together externally.

For pin location and package outline drawings, see back pages.